

EMG 15 ton power press

State	NEW
Category	Press
Brand	EMG
Model	15T
Serial number	-
Year of manufacture	-
Inventory number	100026



CHARACTERISTICS

With electro-pneumatic mono-disc clutch

Technical data

Adjustable stroke: from 5 to 75 mm
 Swan-neck depth: 180 mm
 Shut Height: 300 mm
 Stroke per minute: 140
 Press ram adjustment: from 0 to 50 mm

Standard equipment

20° tiltable frame
 6-digit counter with reset switch
 8-digit counter without reset switch
 Centralised lubrication by hand pump
 Bi-manual push-button safety control
 Stroke-by-stroke or continuous working
 Ejection bar in the press slider

COMPOSITION AND ACCESSORIES

Options (non-included)

Automatic vertical shield with pedal control
 Pedal control for machine without movable shielding
 SICK safety opto-electronic device : simple and double passage
 Unblocking wedge system for the slider at the dead bottom centre
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve
 Additional cam to collect information (feeder control, ...)
 Electronic cams Omron with 8 outlets
 Special selector for outside control (cycle departure outside of the press)
 6-digit counter pre-selector
 Automatic lubrication with level control (normal use)
 Automatic lubrication with level control (intensive use-outflow x 4)
 Rubber cushion
 Worktable halogen lighting : 50W with 500 mm flex
 Worktable lighting : 2 neon tubes (18 W, only if Safety Opto-Electronic device)
 Variable speed drive with selection by potentiometer (220 V mono)
 Exhaust pipe to decrease the sound level (2 dB)
 Metal sheet under press slider to collect oil (loss of 8 mm for clearance height)

Set of 2 anvil stakes DIN 508 M12 for T-grooves
 Set of 4 anti-vibration supports diameter 90 mm
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)
 Band feeder Straightener Decoiler

