

# EMG 15 ton power press

<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	15T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100026



## CHARACTERISTICS

With electro-pneumatic mono-disc clutch

### Technical data

Adjustable stroke: from 5 to 75 mm  
 Swan-neck depth: 180 mm  
 Shut Height: 300 mm  
 Stroke per minute: 140  
 Press ram adjustment: from 0 to 50 mm

### Standard equipment

20° tiltable frame  
 6-digit counter with reset switch  
 8-digit counter without reset switch  
 Centralised lubrication by hand pump  
 Bi-manual push-button safety control  
 Stroke-by-stroke or continuous working  
 Ejection bar in the press slider

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Automatic vertical shield with pedal control  
 Pedal control for machine without movable shielding  
 SICK safety opto-electronic device : simple and double passage  
 Unblocking wedge system for the slider at the dead bottom centre  
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve  
 Additional cam to collect information (feeder control, ...)  
 Electronic cams Omron with 8 outlets  
 Special selector for outside control (cycle departure outside of the press)  
 6-digit counter pre-selector  
 Automatic lubrication with level control (normal use)  
 Automatic lubrication with level control (intensive use-outflow x 4)  
 Rubber cushion  
 Worktable halogen lighting : 50W with 500 mm flex  
 Worktable lighting : 2 neon tubes (18 W, only if Safety Opto-Electronic device)  
 Variable speed drive with selection by potentiometer (220 V mono)  
 Exhaust pipe to decrease the sound level (2 dB)  
 Metal sheet under press slider to collect oil (loss of 8 mm for clearance height) .....  
 Set of 2 anvil stakes DIN 508 M12 for T-grooves  
 Set of 4 anti-vibration supports diameter 90 mm  
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)  
 Band feeder Straightener Decoiler

