

EMG 6 Ton power press

State	NEW
Category	Press
Brand	EMG
Model	6T
Serial number	-
Year of manufacture	-
Inventory number	100025



CHARACTERISTICS

Adjustable stroke: from 4 to 40 mm
 Swan-neck depth: 120 mm
 Shut Height: 200 mm
 Stroke per minute: 240
 Press ram adjustment: from 0 to 30 mm

Standard equipment

20° tiltable frame
 6-digit counter with reset switch
 8-digit counter without reset switch
 Centralised lubrication by hand pump
 Bi-manual push-button safety control
 Stroke-by-stroke or continuous working
 Ejection bar in the press slider

COMPOSITION AND ACCESSORIES

Options (non-included)

Automatic vertical shield with pedal control
 Pedal control for machine without movable shielding
 Unblocking wedge system for the slider at the dead bottom centre
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve
 Additional cam to collect information (feeder control, ...)
 Electronic cams Omron with 8 outlets
 Special selector for outside control (cycle departure outside of the press)
 6-digit counter pre-selector
 Automatic lubrication with level control
 Automatic lubrication with level control (intensive use-outflow x 4)
 Rubber cushion
 Worktable halogen lighting : 50W with 500 mm flex
 Variable speed drive with selection by potentiometer (220 V mono)
 Exhaust pipe to decrease the sound level (2 dB)
 Metal sheet under press slider to collect oil (loss of 6 mm for clearance height)
 Set of 2 anvil stakes DIN 508 M10 for T-grooves
 Set of 4 anti-vibration supports diameter 80 mm .
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)
 Band feeder - Straightener - Decoiler

