

# EMG 6 Ton power press

<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	6T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100025



## CHARACTERISTICS

Adjustable stroke: from 4 to 40 mm  
 Swan-neck depth: 120 mm  
 Shut Height: 200 mm  
 Stroke per minute: 240  
 Press ram adjustment: from 0 to 30 mm

### Standard equipment

20° tiltable frame  
 6-digit counter with reset switch  
 8-digit counter without reset switch  
 Centralised lubrication by hand pump  
 Bi-manual push-button safety control  
 Stroke-by-stroke or continuous working  
 Ejection bar in the press slider

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Automatic vertical shield with pedal control  
 Pedal control for machine without movable shielding  
 Unblocking wedge system for the slider at the dead bottom centre  
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve  
 Additional cam to collect information (feeder control, ...)  
 Electronic cams Omron with 8 outlets  
 Special selector for outside control (cycle departure outside of the press)  
 6-digit counter pre-selector  
 Automatic lubrication with level control  
 Automatic lubrication with level control (intensive use-outflow x 4)  
 Rubber cushion  
 Worktable halogen lighting : 50W with 500 mm flex  
 Variable speed drive with selection by potentiometer (220 V mono)  
 Exhaust pipe to decrease the sound level (2 dB)  
 Metal sheet under press slider to collect oil (loss of 6 mm for clearance height)  
 Set of 2 anvil stakes DIN 508 M10 for T-grooves  
 Set of 4 anti-vibration supports diameter 80 mm .  
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)  
 Band feeder - Straightener - Decoiler

